

TECHNICAL SPECIFICATION

1. GENERAL

1.1 Scope

Cable type	Application
ADSS	Self-supporting aerial installation cable

1.2 Reference

The following international specifications were used as reference documents for the cables provided by Navigator:

IEC 60793-1	Optical fiber Part 1: Generic specifications
IEC 60793-2	Optical fiber Part 2: Product specifications
ITU-T G.650	Definition and test methods for the relevant parameters of single-mode fibers
ITU-T G.652	Characteristics of a single-mode optical fiber and cable
EIA/TIA 598	Color code of fiber optic cables
IEEE Std 1222-2019	IEEE Standard for Testing and Performance for All-Dielectric Self-Supporting (ADSS) Fiber Optic Cable for Use on Electric Utility Power Lines

1.3 QR Guard™

QR Guard™ is a multifunctional online platform that revolutionizes how distributors and network operators keep tabs on the status of Navigator fiber cables, ensuring efficient operations, accurate record-keeping, and valuable insights for future product development. Providing unique features including:

- Distributor exclusive management interface
- Installation record archiving
- Written guidelines and visual demonstrations

QR Guard™ plays a vital role in mitigating the costly consequences of mishandling while enabling efficient network expansion in response to evolving market demands. Scan the QR code in the bottom left corner to find our more.



2. OPTICAL FIBER


ITU-T G.652.D		
Category	Description	Specifications
Optical Specifications	Attenuation @1310 nm	≤ 0.36 dB/km
	Attenuation @1550 nm	≤ 0.23 dB/km
	Zero Dispersion Wavelength	1300~1324 nm
	Chromatic dispersion @1310nm @1550nm @1625nm	≤ 3.5 ps/(nm·km) ≤ 18 ps/(nm·km) ≤ 22 ps/(nm·km)
	Zero Dispersion Slope	≤ 0.092 ps/nm ² ·km
	PMD _Q	≤ 0.20 ps/√km
	PMD individual value	≤ 0.2 ps/√km
	Cable Cutoff Wavelength (λ_{cc})	≤ 1260 nm
	Macro bending Loss (100 turns; $\Phi 60$ mm) @1625 nm	≤ 0.10 dB
	Mode Field Diameter @1310 nm	(8.6-9.2) $\pm 0.4\mu\text{m}$
Dimensional Specifications	Cladding Diameter	125 $\pm 0.7\mu\text{m}$
	Coating diameter	245 $\pm 10\mu\text{m}$
	Core/clad concentricity error	$\leq 0.6\mu\text{m}$
	Cladding Non-Circularity	< 1.0%
Mechanical Specifications	Proof stress	≥ 0.69 Gpa



3. CABLE STRUCTURE

3.1 Cable type

ADSS



Features & Application

- Excellent excess length control technology guarantees superb mechanical and environmental performances
- More environmentally friendly water-blocking materials
- Aramid yarns can provide excellent and stable tension performance

Dimensions and Properties

	Fiber type	ITU-T G.652.D
Physical	Fiber count	144
	No. of fibers per tube	12
	Cable OD mm(in)	16.0(0.63)
	Cable weight kg/km(lb/1000ft)	125(84)
	Condition	NESC Heavy
Properties	Operation temperature range	-40°C to + 70 °C (-40 ° F to 158 ° F)
	Installation temperature range	-30 °C to + 60 °C (-22 ° F to 140 ° F)
	Transport and storage temperature range	-40 °C to + 70 °C (-40 ° F to 158 ° F)
	Max. tensile load (MAT) – N(lb)	4950(1114)
	Crush resistance N/10cm(lb/in)	5000(57)
	SAG %	4.1%
	Span(m)	100
	Minimal installation bending radius	20*D
Minimal operation bending radius	10*D	

*Note: D =cable diameter



4. TEST REQUIREMENTS

Fiber test standard

Mode field diameter	IEC 60793-1-45
Mode field Core/clad concentricity	IEC 60793-1-20
Cladding diameter	IEC 60793-1-20
Cladding non-circularity	IEC 60793-1-20
Attenuation coefficient	IEC 60793-1-40
Chromatic dispersion	IEC 60793-1-42
Cable cut-off wavelength	IEC 60793-1-44

Performance testing list

4.1 Tensile strength test

Test Standard	IEC 60794-1-21 E1
Sample length	No less than 50 meters
Load	MRCL
Duration time	1 minute
Test results	Fiber strain $\leq 0.20\%$ Additional attenuation $\leq 0.10\text{dB}$
	No damage to outer jacket and inner elements

4.2 Compressive strength test

Test Standard	IEC 60794-1-21 E3
Load	Crush resistance
Duration time	1minute
Test number	3
Test results	Additional attenuation $\leq 0.10\text{dB}$
	No damage to outer jacket and inner elements under short term load

4.3 Impact resistance test

Test Standard	IEC 60794-1-21 E4
Impact energy	5J
Radius	10mm



Impact points	3
Impact number	1
Test result	Additional attenuation $\leq 0.10\text{dB}$
	No damage to outer jacket and inner elements

4.4 Cyclic flexing test

Test Standard	IEC 60794-1-21 E6
Bending radius	20*D
Number of cycles	25
Load	250N
Test result	Additional attenuation $\leq 0.10\text{dB}$
	No damage to outer jacket and inner elements

4.5 Twist test

Test Standard	IEC 60794-1-21 E7
Sample length	2m
Angles	± 180 degree
Load	20N
Cycles	10
Test result	Additional attenuation $\leq 0.10\text{dB}$
	No damage to cable elements

4.6 Abrasion test

Test Standard	IEC 60794-1-21 E2B
Experiment method	The wool felt should be thoroughly impregnated with water
Frequency	50cycles/min
Load	20N
Cycles	10
Test result	The marking should be legible after test

4.7 Bend

Test Standard	IEC 60794-1-21 E11
Mandrel diameter	20*D
Turn number	3
Number of cycles	4
Test result	Additional attenuation $\leq 0.10\text{dB}$
	No damage to outer jacket and inner elements



4.8 Temperature cycling test

Test Standard	IEC 60794-1-22 F1
Temperature step	+20 °C → -40 °C → +70 °C → +20 °C
Time per each step	12 hours
Cycles	2
Test result	Attenuation variation for reference value (the attenuation to be measured before test at +20±3 °C) ≤ 0.15dB/km

4.9 Water penetration

Test Standard	IEC 60794-1-22 F5
Height of water column	1m
Sample length	3m
Test time	24 hours
Test result	No water seepage from the opposite end of the sample

4.10 Environmental performance

Test Standard	RoHS
Test result	Pass the test.

Remark: The test wavelength is 1550 nm.

5. COLOR CODE SCHEME

Fiber color	blue	orange	green	brown	slate	white	red	black	yellow	violet	pink	aqua
Tube color	blue	orange	green	brown	slate	white	red	black	yellow	violet	pink	aqua

6. SHEATH MARKING

